



## FIRE FIGHTING AND WASHDOWN LAY FLAT HOSE

### HEAVY DUTY FIRE HOSE WITH ADDED PROTECTION

This hose is a popular choice with both fire brigades and oilfield plant fire protection. It is manufactured with an extruded synthetic rubber cover which protects the hose against abrasion and chemical damage. This woven fire hose is made from polyester with a synthetic rubber lining and cover. The interior lining and exterior coating on the fire hose jacket is made from PVC nitrile which is highly chemical and abrasion resistant and is protected from being stained by oils and dirt.

UV stabilised so it stands up well to prolonged outdoor use. Manufactured in an ISO 9001 quality accredited factory complete with a standard 12 month warranty. Also has approval to Australian Standard AS 2792-1992 and the Australian Army Standard DEF 5195A-1992.

It is mainly used for:

- Fire fighting
- Wash-down
- Water transfer

Usually supplied in 30m lengths but longer lengths, up to 200m, can be manufactured. It is easy to store and is also

CLASS AS2792	ID (mm)	ID (inches)	WP (kpa)	TP (kpa)	BP (kpa)
M	25	1"	1400	2100	4000
M	38	1½"	1400	2100	3750
M	45	1¾"	1400	2100	3500
M	50	2"	1400	2100	5000
M	64	2½"	1400	2100	5000
M	76	3"	1400	2100	3500
H	25	1"	2100	3150	6400
H	38	1½"	2100	3150	5300
H	45	1¾"	2100	3150	5250
H	50	2"	2100	3150	5250
H	64	2½"	2100	3150	5250