

WHEN INTEGRITY IS EVERYTHING!



H Series Non Skive Hydraulic Fittings
-20, -24 & -32 sizes (1-1/4" thru 2')

PROTECT YOUR INVESTMENT

Video Link:

www.pirtek.co.nz/products/productcategory/new-products-and-promotions/h-series-non-skive-hydraulic-fittings

 **intertraco**

WE'LL KEEP YOU OPERATING

0800 747 835

Nationwide Service 24 hours - 7 days

www.pirtek.co.nz

Lock connections between shell and reinforcement assures safe and leak-free long service life

Teeth of shell bite down onto wire providing metal-to-metal grip



Faster assembly times & less cleanup

Maintains the integrity of the hose

No skiving required so hose & fitting are ready to assemble

H Series Non Skive Hydraulic Fittings

-20, -24 & -32 sizes (1-1/4" thru 2')

Structural integrity of the hose remains whole as the weatherproofing external rubber is untouched in the assembly process reducing the effect of environmental corrosion.

Mild steel & stainless
Straight, 45 & 90°

Male & female threads plus flange termination

HEAVY DUTY TEETH



ATTRIBUTES



THREAD TYPES

BSP	JIC
NPT MALE	ORFS
DKS METRIC	SAE CODE 61
SAE CODE 62	LE TORNEAU
CAT®	KOMATSU