



TRU-FIT 10K FITTINGS



TruFit 10K Pipe and Adapter Fittings are designed and manufactured to provide a reliable connection in high pressure systems running to 10,000 psi. Manufactured from fully-traceable raw material to close tolerances and superior surface finishes.

SPECIFICATION AND APPLICATION GUIDELINES

APPLICATION PARAMETER	TAPERED THREAD	PARALLEL THREAD
Pressures	High to 10,000 psi (static systems only)	High to 10,000 psi (static & dynamic systems)
Temperatures	Stainless: -425° to 1200°F	Nitrile/Buna: -30° to 250°F Viton: -15° to 400°F
Vibration Resistance	Poor	Very Good
Materials	316/316L stainless steel to ASTM A-276 and A-479 bar stock, A-182 forgings.	316/316L stainless steel to ASTM A-276 and A-479 bar stock, A182 forgings
Size Available (nominal)	1/8" – 1"	#4 - #16
Seal Reliability	Good in static systems. Poor in dynamic systems. Medium tolerance to minor thread imperfections. Medium tolerance to assembly variation	Excellent in static systems; Very good in dynamic systems. Medium tolerance to thread & taper angle imperfections
Thread & Port Preparation	Anaerobic sealant, or pipe thread sealant or tape	General lubricant applied to threads
Ease of Assembly	Medium L1 thread gauge & basic assembly practices must be followed	High Intuitive make-up. Repeatable process
Ease of Maintenance	Limited breaks and remakes due to metal deformation of threads	Very good. Virtually unlimited breaks & remakes. O-ring replacement only
Specification Conformance (design, thread and pressure)	NPT: ANSI B1.20.1 and AS-7105 (frm. MIL-P-7105B) ISO/BSPT: ISO 7/1, JIS B0203, BS EN 10226-1	SAE: J1926, ISO 11926, ASME B1.1, ISO 263 ISO/BSPP: ISO 228, JIS B0202
Pressure Rating	ASME B31.3	ASME B31.3

Brand
Designator
T=TruFit

1st end
connection
description

2nd end
connection
description

ISS T 4 AN 4 MC -10K

Instrumentation
Material
Designator

1st end
connection size
(chart 1)

2nd end
connection size
(chart 1)

Indicates a
10,000 psi
rated fitting

CHART 2

Description of Fitting	Fitting designator
Adapter	A
37° AN Union	AN-AN
AN Cap	ANCP
37° AN Swivel Union	ANF-ANF
37°AN x 37° Swivel AN	AN-ANF
37° AN Swivel x Male NPT	ANF-MC
AN Swivel Elbow	AN-FE
AN Male Elbow	AN-ME
37° AN Swivel x Male ISO Straight	ANF-MRS
37° AN x Male NPT	AN-MC
37° AN x Male SAE	AN-MST
AN Plug	ANP
AN Union Elbow	ANUE
Elbow	E
Hex Coupling	HC
Hex Long Nipple	HLN
Hex Nipple	HN
Hex Reducing Coupling	HRC
Hex Reducing Nipple	HRN
Male NPT x Male ISO Straight	MC-MRS
Male NPT x Male SAE	MC-MST
Male Elbow	ME
BSP Nipple	MRS-MRS
Male ISO Straight x Male SAE	MRS-MST
Male Tee	MT
Pipe Cap	PC
Pipe Plug	PP
Pipe Tee	PT
Street Elbow	SE
Reducing Bushing	RB

CHART 1

Size	Part No. Size
1	1/16"
2	1/8"
4	1/4"
6	3/8"
8	1/2"
12	3/4"
16	1"
20	1-1/4"
32	2"

CLEANLINESS

TruFit components are cleaned in accordance with documented work instructions using equipment calibrated to NIST standards with environmentally-safe and stable agents, ultrasonics, and heat/temperature to remove all residual oil, grease and loose particles. Stainless steel components are passivated to the requirements of MIL QQ-P-35 and ASTM A 967. Components are also available specially cleaned and packaged for oxygen service to ensure compliance with the product cleanliness requirements as stated in CGA G-4.1 and ASTM G 93 Level C.

SAFETY

To help ensure the safe and reliable performance of TruFit products, complete system design must be considered prior to installation of the pipe, tubing and fittings. Determining the design compatibility of materials, media, flows, temperatures and pressures; as well as implementing proper installation, operation and maintenance of the system are the responsibility of the systems' owners, designers and users.

- Do not install, tighten or loosen a fitting or adapter while the system is under pressure.
- Do not loosen a fitting, nut or plug to relieve or bleed system pressure.
- Always use a back-up wrench to hold the pipe or pipe fitting body steady when tightening or loosening.
- Use proper thread lubricants and sealants on tapered pipe threads.
- Tube fitting end connection and tubing material should be similar (stainless steel fittings on stainless steel tubing, brass fittings on copper tubing, etc.) with the tubing material being fully annealed.
- Do not weld tube fittings that are assembled.
- Prior to welding, remove all components such as nut, ferrule(s), o-ring, and seals. Protect the sealing and thread areas of the tube fitting by covering with a plug or another nut.



CONTENTS

PRODUCT	PAGE NO.
HN - NPT x NPT Hex Nipple_____	1
HRN - Hex Reducing Nipple_____	1
HRN - NPT x NPT Hex Long Nipple_____	2
MRS-MRS - BSPP x BSPP Hex Nipple_____	2
MC-MRS - NPT x BSPP Hex Nipple_____	3
MRS-MST - BSPP x SAE Hex Nipple_____	4
AN UNION_____	4
ADAPTER_____	5
REDUCING ADAPTER_____	5
REDUCING BUSH_____	6
PIPE CAP_____	6
ELBOW_____	7
MALE ELBOW_____	7
STREET ELBOW_____	7
PIPE PLUG_____	8
PIPE TEE_____	8
MALE TEE_____	8
HEX COUPLING_____	9
HEX REDUCING COUPLING_____	9
AN MALE CONNECTOR_____	10
AN & SAE MALE CONNECTOR_____	10
AN MALE ELBOW_____	11
AN FEMALE ELBOW_____	11
AN UNION ELBOW_____	12
AN X BSPP MALE CONNECTOR_____	12
AN CAP_____	13
AN PLUG_____	13



HN NPT x NPT Hex Nipple

PRODUCT CODE	DESCRIPTION
OGT2HN-10K	1/8" NPT Hex nipple s/s 10k
OGT4HN-10K	1/4" NPT Hex nipple s/s 10k
OGT6HN-10K	3/8" NPT Hex nipple s/s 10k
OGT8HN-10K	1/2" NPT Hex nipple s/s 10k
OGT12HN-10K	3/4" NPT Hex nipple s/s 10k
OGT16HN-10K	1" NPT Hex nipple s/s 10k
OGT32HN-10K	2" NPT Hex nipple s/s 10k



HRN Hex Reducing Nipple

PRODUCT CODE	DESCRIPTION
OGT4HRN2-10K	1/4" x 1/8" NPT Hex Reducing nipple s/s 10k
OGT6HRN2-10K	3/8" x 1/8" NPT Hex Reducing nipple s/s 10k
OGT6HRN4-10K	3/8" x 1/4" NPT Hex Reducing nipple s/s 10k
OGT8HRN2-10K	1/2" x 1/8" NPT Hex Reducing nipple s/s 10k
OGT8HRN4-10K	1/2" x 1/4" NPT Hex Reducing nipple s/s 10k
OGT8HRN6-10K	1/2" x 3/8" NPT Hex Reducing nipple s/s 10k
OGT12HRN4-10K	3/4" x 1/4" NPT Hex Reducing nipple s/s 10k
OGT12HRN6-10K	3/4" x 3/8" NPT Hex Reducing nipple s/s 10k
OGT12HRN8-10K	3/4" x 1/2" NPT Hex Reducing nipple s/s 10k
OGT16HRN4-10K	1" x 1/4" NPT Hex Reducing nipple s/s 10k
OGT16HRN6-10K	1" x 3/8" NPT Hex Reducing nipple s/s 10k
OGT16HRN8-10K	1" x 1/2" NPT Hex Reducing nipple s/s 10k
OGT16HRN12-10K	1" x 3/4" NPT Hex Reducing nipple s/s 10k



HRN NPT x NPT Hex Long Nipple

PRODUCT CODE	DESCRIPTION
OGT2HLN3.0-10K	1/8" NPT x 3 inch long hex long nipple s/s 10k
OGT4HLN2.0-10K	1/4" NPT x 2 inch long hex long nipple s/s 10k
OGT4HLN3.0-10K	1/4" NPT x 3 inch long hex long nipple s/s 10k
OGT4HLN4.0-10K	1/4" NPT x 4 inch long hex long nipple s/s 10k
OGT4HLN6.0-10K	1/4" NPT x 6 inch long hex long nipple s/s 10k
OGT6HLN3.0-10K	3/8" NPT x 3 inch long hex long nipple s/s 10k
OGT6HLN4.0-10K	3/8" NPT x 4 inch long hex long nipple s/s 10k
OGT6HLN6.0-10K	3/8" NPT x 6 inch long hex long nipple s/s 10k
OGT8HLN1.5-10K	1/2" NPT x 1.5 inch long hex long nipple s/s 10k
OGT8HLN1.75-10K	1/3" NPT x 1.75 inch long hex long nipple s/s 10k
OGT8HLN3.0-10K	1/2" NPT x 3 inch long hex long nipple s/s 10k
OGT8HLN4.0-10K	1/2" NPT x 4 inch long hex long nipple s/s 10k
OGT8HLN6.0-10K	1/2" NPT x 6 inch long hex long nipple s/s 10k



MRS-MRS BSPP x BSPP Hex Nipple

PRODUCT CODE	DESCRIPTION
OGT2MRS2MRS-10K	1/8" x 1/8" BSPP Hex Nipple s/s 10k
OGT4MRS2MRS-10K	1/4" x 1/8" BSPP Hex Nipple s/s 10k
OGT4MRS4MRS-10K	1/4" x 1/4" BSPP Hex Nipple s/s 10k
OGT6MRS4MRS-10K	3/8" x 1/4" BSPP Hex Nipple s/s 10k
OGT6MRS6MRS-10K	3/8" x 3/8" BSPP Hex Nipple s/s 10k
OGT8MRS2MRS-10K	1/2" x 1/8" BSPP Hex Nipple s/s 10k
OGT8MRS4MRS-10K	1/2" x 1/4" BSPP Hex Nipple s/s 10k
OGT8MRS6MRS-10K	1/2" x 3/8" BSPP Hex Nipple s/s 10k
OGT8MRS8MRS-10K	1/2" x 1/2" BSPP Hex Nipple s/s 10k
OGT10MRS10MRS-10K	5/8" x 5/8" BSPP Hex Nipple s/s 10k
OGT12MRS8MRS-10K	3/4" x 1/2" BSPP Hex Nipple s/s 10k
OGT16MRS12MRS-10K	1" x 3/4" BSPP Hex Nipple s/s 10k
OGT12MRS12MRS-10K	3/4" x 3/4" BSPP Hex Nipple s/s 10k
OGT16MRS16MRS-10K	1" x 1" BSPP Hex Nipple s/s 10k



MC-MRS NPT x BSPP Hex Nipple

PRODUCT CODE	DESCRIPTION
OGT2MC2MRS-10K	1/8" NPT male x 1/8" BSPP male s/s 10k
OGT4MC2MRS-10K	1/4" NPT male x 1/8" BSPP male s/s 10k
OGT4MC4MRS-10K	1/4" NPT male x 1/4" BSPP male s/s 10k
OGT2MC4MRS-10K	1/8" NPT male x 1/4" BSPP male s/s 10k
OGT6MC4MRS-10K	3/8" NPT male x 1/4" BSPP male s/s 10k
OGT8MC4MRS-10K	1/2" NPT male x 1/4" BSPP male s/s 10k
OGT4MC6MRS-10K	1/4" NPT male x 3/8" BSPP male s/s 10k
OGT6MC6MRS-10K	3/8" NPT male x 3/8" BSPP male s/s 10k
OGT8MC6MRS-10K	1/2" NPT male x 3/8" BSPP male s/s 10k
OGT4MC8MRS-10K	1/4" NPT male x 1/2" BSPP male s/s 10k
OGT6MC8MRS-10K	3/8" NPT male x 1/2" BSPP male s/s 10k
OGT8MC8MRS-10K	1/2" NPT male x 1/2" BSPP male s/s 10k
OGT12MC8MRS-10K	3/4" NPT male x 1/2" BSPP male s/s 10k
OGT16MC8MRS-10K	1" NPT male x 1/2" BSPP male s/s 10k
OGT8MC10MRS-10K	1/2" NPT male x 5/8" BSPP male s/s 10k
OGT8MC12MCRS-10K	1/2" NPT male x 3/4" BSPP male s/s 10k
OGT12MC12MRS-10K	3/4" NPT male x 3/4" BSPP male s/s 10k
OGT16MC12MRS-10K	1" NPT male x 3/4" BSPP male s/s 10k
OGT12MC16MRS-10K	3/4" NPT male x 1" BSPP male s/s 10k
OGT16MC16MRS-10K	1" NPT male x 1" BSPP male s/s 10k
OGT16MC20MRS-10K	1" NPT male x 1-1/4" BSPP male s/s 10k



MRS-MST

BSPP x SAE Hex Nipple

PRODUCT CODE	DESCRIPTION
OGT4MRS4MSOGT-10K	1/4" BSPP x 1/4" SAE male s/s 10k
OGT8MRS8MSOGT-10K	1/2" BSPP x 1/2" SAE male s/s 10k
OGT4MC4MSOGT-10K	1/4" NPT x 1/4" SAE male s/s 10k
OGT8MC8MSOGT-10K	1/2" NPT x 1/4" SAE male s/s 10k



AN UNION

PRODUCT CODE	DESCRIPTION
OGT4AN4AN-10K	7/16" JIC x 7/16" JIC Nipple s/s 10k
OGT5AN5AN-10K	1/2" JIC x 1/2" JIC Nipple s/s 10k
OGT6AN6AN-10K	9/16" JIC x 9/16" JIC Nipple s/s 10k
OGT8AN8AN-10K	3/4" JIC x 3/4" JIC Nipple s/s 10k
OGT10AN10AN-10K	7/8" JIC x 7/8" JIC Nipple s/s 10k
OGT12AN12AN-10K	1-1/16" JIC x 1-1/16" JIC Nipple s/s 10k
OGT16AN16AN-10K	1-5/16" JIC x 1-5/16" JIC Nipple s/s 10k



ADAPTER

PRODUCT CODE	DESCRIPTION
OGT4A-10K	1/4" NPT female to 1/4" NPT male s/s 10k
OGT6A-10K	3/8" NPT female to 3/8" NPT male s/s 10k
OGT8A-10K	1/2" NPT female to 1/2" NPT male s/s 10k
OGT12A-10K	3/4" NPT female to 3/4" NPT male s/s 10k
OGT16A-10K	1" NPT female to 1" NPT male s/s 10k



REDUCING ADAPTER

PRODUCT CODE	DESCRIPTION
OGT4RA2-10K	1/4" NPT female to 1/8" NPT male s/s 10k
OGT6RA2-10K	3/8" NPT female to 1/8" NPT male s/s 10k
OGT6RA4-10K	3/8" NPT female to 1/4" NPT male s/s 10k
OGT8RA2-10K	1/2" NPT female to 1/8" NPT male s/s 10k
OGT8RA4-10K	1/2" NPT female to 1/4" NPT male s/s 10k
OGT8RA6-10K	1/2" NPT female to 3/8" NPT male s/s 10k
OGT12RA4-10K	3/4" NPT female to 1/4" NPT male s/s 10k
OGT12RA6-10K	3/4" NPT female to 3/8" NPT male s/s 10k
OGT12RA8-10K	3/4" NPT female to 1/2" NPT male s/s 10k
OGT16RA8-10K	1" NPT female to 1/2" NPT male s/s 10k
OGT16RA12-10K	1" NPT female to 3/4" NPT male s/s 10k



REDUCING BUSH

PRODUCT CODE	DESCRIPTION
OGT4RB2-10K	1/4" NPT male to 1/8" NPT female bush s/s 10k
OGT8RB2-10K	1/2" NPT male to 1/8" NPT female bush s/s 10k
OGT6RB4-10K	3/8" NPT male to 1/4" NPT female bush s/s 10k
OGT8RB4-10K	1/2" NPT male to 1/4" NPT female bush s/s 10k
OGT12RB4-10K	3/4" NPT male to 1/4" NPT female bush s/s 10k
OGT16RB4-10K	1" NPT male to 1/4" NPT female bush s/s 10k
OGT8RB6-10K	1/2" NPT male to 3/8" NPT female bush s/s 10k
OGT12RB6-10K	3/4" NPT male to 3/8" NPT female bush s/s 10k
OGT16RB6-10K	1" NPT male to 3/8" NPT female bush s/s 10k
OGT12RB8-10K	3/4" NPT male to 1/2" NPT female bush s/s 10k
OGT16RB8-10K	1" NPT male to 1/2" NPT female bush s/s 10k
OGT32RB8-10K	2" NPT male to 1/2" NPT female bush s/s 10k
OGT16RB12-10K	1" NPT male to 3/4" NPT female bush s/s 10k



PIPE CAP

PRODUCT CODE	DESCRIPTION
OGT2PCP-10K	1/8" NPT Pipe Cap s/s 10k
OGT4PCP-10K	1/4" NPT Pipe Cap s/s 10k
OGT6PCP-10K	3/8" NPT Pipe Cap s/s 10k
OGT8PCP-10K	1/2" NPT Pipe Cap s/s 10k
OGT12PCP-10K	3/4" NPT Pipe Cap s/s 10k
OGT16PCP-10K	1" NPT Pipe Cap s/s 10k



ELBOW

PRODUCT CODE	DESCRIPTION
OGT2E-10K	1/8" NPT Female 90 deg elbow s/s 10k
OGT4E-10K	1/4" NPT Female 90 deg elbow s/s 10k
OGT6E-10K	3/8" NPT Female 90 deg elbow s/s 10k
OGT8E-10K	1/2" NPT Female 90 deg elbow s/s 10k



MALE ELBOW

PRODUCT CODE	DESCRIPTION
OGT4ME-10K	1/4" NPT male 90 deg elbow s/s 10k
OGT6ME-10K	3/8" NPT male 90 deg elbow s/s 10k
OGT8ME-10K	1/2" NPT male 90 deg elbow s/s 10k



STREET ELBOW

PRODUCT CODE	DESCRIPTION
OGT2SE-10K	1/8" NPT male female 90 deg elbow s/s 10k
OGT4SE-10K	1/4" NPT male female 90 deg elbow s/s 10k
OGT6SE-10K	3/8" NPT male female 90 deg elbow s/s 10k
OGT8SE-10K	1/2" NPT male female 90 deg elbow s/s 10k



PIPE PLUG

PRODUCT CODE	DESCRIPTION
OGT2PP-10K	1/8" NPT Pipe Plug s/s 10k
OGT4PP-10K	1/4" NPT Pipe Plug s/s 10k
OGT6PP-10K	3/8" NPT Pipe Plug s/s 10k
OGT8PP-10K	1/2" NPT Pipe Plug s/s 10k
OGT12PP-10K	3/4" NPT Pipe Plug s/s 10k
OGT16PP-10K	1" NPT Pipe Plug s/s 10k



PIPE TEE

PRODUCT CODE	DESCRIPTION
OGT2POGT-10K	1/8" NPT Female Tee s/s 10k
OGT4POGT-10K	1/4" NPT Female Tee s/s 10k
OGT6POGT-10K	3/8" NPT Female Tee s/s 10k
OGT8POGT-10K	1/2" NPT Female Tee s/s 10k



MALE TEE

PRODUCT CODE	DESCRIPTION
OGT4MOGT-10K	1/4" NPT Male Tee s/s 10k
OGT6MOGT-10K	3/8" NPT Male Tee s/s 10k
OGT8MOGT-10K	1/2" NPT Male Tee s/s 10k



HEX COUPLING

PRODUCT CODE	DESCRIPTION
OGT2HCG-10K	1/8" NPT Hex coupling s/s 10k
OGT4HCG-10K	1/4" NPT Hex coupling s/s 10k
OGT6HCG-10K	3/8" NPT Hex coupling s/s 10k
OGT8HCG-10K	1/2" NPT Hex coupling s/s 10k
OGT12HCG-10K	3/4" NPT Hex coupling s/s 10k
OGT16HCG-10K	1" NPT Hex coupling s/s 10k



HEX REDUCING COUPLING

PRODUCT CODE	DESCRIPTION
OGT2HCG-10K	1/8" NPT Hex coupling s/s 10k
OGT4HCG-10K	1/4" NPT Hex coupling s/s 10k
OGT6HCG-10K	3/8" NPT Hex coupling s/s 10k
OGT8HCG-10K	1/2" NPT Hex coupling s/s 10k
OGT12HCG-10K	3/4" NPT Hex coupling s/s 10k
OGT16HCG-10K	1" NPT Hex coupling s/s 10k



AN MALE CONNECTOR

PRODUCT CODE	DESCRIPTION
OGT4AN4MC-10K	7/16" JIC x 1/4" NPT Nipple s/s 10k
OGT4AN6MC-10K	7/16" JIC x 3/8" NPT Nipple s/s 10k
OGT4AN8MC-10K	7/16" JIC x 1/2" NPT Nipple s/s 10k
OGT6AN4MC-10K	9/16" JIC x 1/4" NPT Nipple s/s 10k
OGT6AN6MC-10K	9/16" JIC x 3/8" NPT Nipple s/s 10k
OGT6AN8MC-10K	9/16" JIC x 1/2" NPT Nipple s/s 10k
OGT8AN4MC-10K	3/4" JIC x 1/4" NPT Nipple s/s 10k
OGT8AN6MC-10K	3/4" JIC x 3/8" NPT Nipple s/s 10k
OGT8AN8MC-10K	3/4" JIC x 1/2" NPT Nipple s/s 10k
OGT8AN12MC-10K	3/4" JIC x 3/4" NPT Nipple s/s 10k
OGT12AN8MC-10K	1-1/16" JIC x 1/2" NPT Nipple s/s 10k
OGT12AN12MC-10K	1-1/16" JIC x 3/4" NPT Nipple s/s 10k
OGT16AN8MC-10K	1-5/16" JIC x 1/2" NPT Nipple s/s 10k
OGT16AN12MC-10K	1-5/16" JIC x 3/4" NPT Nipple s/s 10k
OGT16AN16MC-10K	1-5/16" JIC x 1" NPT Nipple s/s 10k



AN & SAE MALE CONNECTOR

PRODUCT CODE	DESCRIPTION
OGT4AN4MSOGT-10K	7/16" JIC x 9/16" ORFS male Nipple s/s 10k
OGT4AN6MSOGT-10K	7/16" JIC x 11/16" ORFS male Nipple s/s 10k
OGT6AN4MSOGT-10K	9/16" JIC x 9/16" ORFS male Nipple s/s 10k
OGT6AN6MSOGT-10K	9/16" JIC x 11/16" ORFS male Nipple s/s 10k
OGT8AN8MSOGT-10K	3/4" JIC x 7/8" ORFS male Nipple s/s 10k



AN MALE ELBOW

PRODUCT CODE	DESCRIPTION
OGT4AN4ME-10K	7/16" JIC M to 1/4" NPT M 90 deg elbow s/s 10k
OGT6AN4ME-10K	9/16" JIC M to 1/4" NPT M 90 deg elbow s/s 10k
OGT6AN6ME-10K	9/16" JIC M to 3/8" NPT M 90 deg elbow s/s 10k
OGT8AN6ME-10K	3/4" JIC M to 3/8" NPT M 90 deg elbow s/s 10k
OGT8AN8ME-10K	3/4" JIC M to 1/2" NPT M 90 deg elbow s/s 10k



AN FEMALE ELBOW

PRODUCT CODE	DESCRIPTION
OGT4AN4ANF-10K	7/16" JIC M x 7/16" JIC Fem Swiv s/s 10k
OGT4AN6ANF-10K	7/16" JIC M x 9/16" JIC Fem Swiv s/s 10k
OGT5AN4ANF-10K	1/2" JIC M x 7/16" JIC Fem Swiv s/s 10k
OGT6AN4ANF-10K	9/16" JIC M x 7/16" JIC Fem Swiv s/s 10k
OGT6AN6ANF-10K	9/16" JIC M x 9/16" JIC Fem Swiv s/s 10k
OGT6AN8ANF-10K	9/16" JIC M x 3/4" JIC Fem Swiv s/s 10k
OGT8AN4ANF-10K	3/4" JIC M x 7/16" JIC Fem Swiv s/s 10k
OGT8AN6ANF-10K	3/4" JIC M x 9/16" JIC Fem Swiv s/s 10k
OGT8AN8ANF-10K	3/4" JIC M x 3/4" JIC Fem Swiv s/s 10k
OGT8AN12ANF-10K	3/4" JIC M x 1-1/16" JIC Fem Swiv s/s 10k
OGT12AN8ANF-10K	1-1/16" JIC M x 3/4" JIC Fem Swiv s/s 10k



AN UNION ELBOW

PRODUCT CODE	DESCRIPTION
OGT4ANUE4-10K	7/16" JIC Male x 7/16" JIC Male 90 deg elbow s/s 10k
OGT6ANUE6-10K	9/16" JIC Male x 9/16" JIC Male 90 deg elbow s/s 10k
OGT8ANUE8-10K	3/4" JIC Male x 3/4" JIC Male 90 deg elbow s/s 10k



AN X BSPP MALE CONNECTOR

PRODUCT CODE	DESCRIPTION
OGT4AN4MRS-10K	7/16" JIC Male x 1/4" BSPP male s/s 10k
OGT4AN6MRS-10K	7/16" JIC Male x 3/8" BSPP male s/s 10k
OGT4AN8MRS-10K	7/16" JIC Male x 1/2" BSPP male s/s 10k
OGT4AN12MRS-10K	7/16" JIC Male x 3/4" BSPP male s/s 10k
OGT6AN6MRS-10K	9/16" JIC Male x 3/8" BSPP male s/s 10k
OGT8AN8MRS-10K	3/4" JIC Male x 3/4" BSPP male s/s 10k



AN CAP

PRODUCT CODE	DESCRIPTION
OGT4ANPCP-10K	7/16" JIC Cap s/s 10k
OGT5ANPCP-10K	1/2" JIC Cap s/s 10k
OGT6ANPCP-10K	9/16" JIC Cap s/s 10k
OGT8ANPCP-10K	3/4" JIC Cap s/s 10k
OGT10ANPCP-10K	7/8" JIC Cap s/s 10k
OGT12ANPCP-10K	1-1/16" JIC Cap s/s 10k
OGT16ANPCP-10K	1-5/16" JIC Cap s/s 10k



AN PLUG

PRODUCT CODE	DESCRIPTION
OGT4ANPCP-10K	7/16" JIC Cap s/s 10k
OGT5ANPCP-10K	1/2" JIC Cap s/s 10k
OGT6ANPCP-10K	9/16" JIC Cap s/s 10k
OGT8ANPCP-10K	3/4" JIC Cap s/s 10k
OGT10ANPCP-10K	7/8" JIC Cap s/s 10k
OGT12ANPCP-10K	1-1/16" JIC Cap s/s 10k
OGT16ANPCP-10K	1-5/16" JIC Cap s/s 10k