




TYPE B SAFETY COUPLINGS (American Style)

INVESTMENT CAST UNIVERSAL HOSE ENDS

Short, Crimp-Specific Shank (left) and Standard Shank (right)

SAFETY AND SAVINGS

Universallock, Single-lock and Doublelock couplings meet OSHA regulation 29CFR1915.131 and MSHA 30 CFR65.13021 requirements for air hose couplings. The fine for an unpinned/unlocked air hose coupling can be \$800 or more per infraction. Save your customer money and headaches. Use Campbell safety air hose couplings.



MAXIMUM SYSTEM WORKING PRESSURE (PSI 70°F)

Hose System Component			Hose Size		
FITTING/COUPLING	ATTACHMENT	HOSE TYPE	1/2	3/4	1
Universallock	Bolt Clamp	Air	300	300	300
Universallock C	lamp	Air	150	150	150
Universal	Ferrule	Air	150	150	150
Universal	Bolt Clamp	Air	150	150	150
Single-Lock Coupling	Ferrule	Air	300	300	300
Double-Lock Coupling	Ferrule	Air	300	300	300



TYPE B SAFETY COUPLINGS (American Style)

MACHINED HOSE TAILS FOR CRIMPING (REFER FERRULE CHART)


NPT SIZE	DUCTILE IRON (MACHINE SERRATIONS)	316 STAINLESS (MACHINE SERRATIONS)	PLATED STEEL (INVESTMENT CAST)
3/8	OGUH-38		
1/2	OGUH-2	OGUHSS-2	OGUH-2i
5/8	OGUH-58		
3/4	OGUH-3	OGUHSS-3	OGUH-3i
1	OGUH-4	OGUHSS-4	OGUH-4i



TYPE B SAFETY COUPLINGS (American Style)

MALE NPT

NPT SIZE	DUCTILE IRON	316 STAINLESS
3/8	OGUM-38	
1/2	OGUM-2	OGUMSS-2
3/4	OGUM-3	OGUMSS-3
1	OGUM-4	OGUMSS-4



TYPE B SAFETY COUPLINGS (American Style)

UNIVERSAL WASHER

NPT SIZE	DUCTILE IRON
All	OGUG
Never use Universal Washers in UniversaLock Couplings	



TYPE B SAFETY COUPLINGS (American Style)

THREE WAY

NPT SIZE	DUCTILE IRON
All	OGUTW



TYPE B SAFETY COUPLINGS (American Style)

TWO-BOLT UNIVERSAL CLAMP

HOSE O.D. (MIN TO MAX)	DUCTILE IRON
3/4 to 15/16	OGUC-2
1 to 1-1/4	OGUC-3
1-1/4 to 1-17/32	OGUC-4



TYPE B SAFETY COUPLINGS (American Style)

BLANK END

NPT SIZE	DUCTILE IRON
All	OGUB



TYPE B SAFETY COUPLINGS (American Style)

SAFETY CLIP

NPT SIZE	DUCTILE IRON
All	OGSC



TYPE B SAFETY COUPLINGS (American style) with Locking Heads

MACHINED HOSE TAILS FOR CRIMPING (REFER FERRULE CHART)

NPT SIZE	DUCTILE IRON MACHINE SERRATIONS
1/2	OGULH-2
3/4	OGULH-3
1	OGULH-4



TYPE B SAFETY COUPLINGS (American style) with Locking Heads

MALE END

NPT SIZE	DUCTILE IRON
1/2	OGULM-2
3/4	OGULM-3
1	OGULM-4



TYPE B SAFETY COUPLINGS (American style) with Locking Heads

UNIVERSALOC WASHER

NPT SIZE	DUCTILE IRON
All	OGULW
Never use Universalock Washers in standard Universal Couplings	



TYPE B SAFETY COUPLINGS (American style) with Locking Heads

FEMALE END

NPT SIZE	DUCTILE IRON
1/2	OGULF-2
3/4	OGULF-3

UNIVERSAL COUPLINGS AND UNIVERSALOC™ COUPLINGS

Features & Benefits

- Mates with domestic and imported universal couplings.
- UniversaLocks automatically lock onto mating coupling.
- Crimpnology hose end for superior retention and sealing.
- Cast ductile iron meets ASTM A536 specification.
- Washers manufactured from nitrile for superior oil resistance.

INVESTMENT CAST UNIVERSAL HOSE ENDS

- Investment casting provides a crisp high quality, hose-end surface-finish without costly machining.
- Crimpnology hose ends for superior retention and sealing.