

RINGLOK

Self-locking camlock

MATERIAL: Stainless Steel/ Aluminium/ Brass

THREAD: NPT/BSP

FEATURES: Easy to operate
Self-locking handles
Resists high pressure
Safe Coupling
Compatible with standard male camlocks

WORKING PRESSURE: from 3/4" up to 2"=362 Psi (25 bar)
from 3" up to 4"=232 Psi (16 bar)



Hose shank design could be customised on request.



ITEM	DESCRIPTION
OGC-316-075CR	3/4" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-316-100CR	1" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-316-150CR	1-1/2" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-316-200CR	2" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-316-300CR	3" CRIMP TAIL X FEM RINGRILOC CAMLOCK SS316
OGC-316-400CR	4" CRIMP TAIL X FEM RINRIGLOC CAMLOCK SS316
OGC-AL-100CR	1" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-AL-150CR	1-1/2" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-AL-200CR	2" CRIMP TAIL X FEM RINGLOK CAMLOCK SS316
OGC-AL-300CR	3" CRIMP TAIL X FEM RINGLOK CAMLOCK ALUM
OGC-AL-400CR	4" CRIMP TAIL X FEM RINGLOK CAMLOCK ALUM
OGD-316-100R	1" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-316-150R	1-1/2" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-316-200R	2" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-316-300R	3" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-316-400R	4" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-AL-100R	1" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-AL-150R	1-1/2" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-AL-200R	2" FEM RINGLOK CAMLOCK x FNPT SS316
OGD-AL-300R	3" FEM RINGLOK CAMLOCK x FNPT ALUM
OGD-AL-400R	4" FEM RINGLOK CAMLOCK x FNPT ALUM