



FRACKING FITTINGS (Crimping Type)

Fracking Fittings are used on hose assemblies that pump drilling muds and fluids on fracking sites. Built to withstand operating pressures of 400psi they are available in three different configurations, Fig 100, 200 and 206 hammer union male and female one piece crimp tail sub. The hose tail is manufactured from plated steel providing superior wear resistance.

Also available with NPT male ends to adapt to other types of end connections. Ferrules are available in plated steel and in various sizes to suit a variety of hoses. Available in male or female ends separately.

PRODUCT CODE	DESCRIPTION
OGCHTF100-050F	2" Fig 100 Female Crimp Hose Tail
OGCHTF100-050M	2" Fig 100 Male Crimp Hose Tail
OGCHTF100-075F	3" Fig 100 Female Crimp Hose Tail
OGCHTF100-075M	3" Fig 100 Male Crimp Hose Tail
OGCHTF100-100M	4" Fig 100 Female Crimp Hose Tail
OGCHTF100-100M	4" Fig 100 Male Crimp Hose Tail
OGCHTF200-050F	2" Fig 200 Female Crimp Hose Tail
OGCHTF200-050M	2" Fig 200 Male Crimp Hose Tail
OGCHTF200-075F	3" Fig 200 Female Crimp Hose Tail
OGCHTF200-075M	3" Fig 200 Male Crimp Hose Tail
OGCHTF200-100M	4" Fig 200 Female Crimp Hose Tail
OGCHTF200-100M	4" Fig 200 Male Crimp Hose Tail
OGCHTF206-050F	2" Fig 206 Female Crimp Hose Tail
OGCHTF206-050M	2" Fig 206 Male Crimp Hose Tail
OGCHTF206-075F	3" Fig 206 Female Crimp Hose Tail
OGCHTF206-075M	3" Fig 206 Male Crimp Hose Tail
OGCHTF206-100M	4" Fig 206 Female Crimp Hose Tail
OGCHTF206-100M	4" Fig 206 Male Crimp Hose Tail