



# HOSE SADDLES DESIGNED TO SUSPEND AND SAFELY HANDLE FLEXIBLE HOSES



## CHARACTERISTICS

- Protect hoses from excessive bending radius and avoid kinking
- Prevent damages caused by abrasion or impacts
- Its special design prevent hose from sliding or twisting
- No maintenance costs
- Reduce risks of accidents, keep work sites safer
- Operating conditions -40 to 130°C (-40 +266°F) with no risk of hydrolysis or aging;
- Anti-spark, insulating, antistatic
- Resistant to hydrocarbons, oil, petrol, kerosene, and many chemicals
- Slings are easily replaceable when worn or damaged
- Available from ¾" to 12"
- Slings compliant with Australian Standards and exceed European Standards



UP 2"



ABOVE 2"

## TECHNICAL DATA

| DIMENSION                 | 1"       | 1.1/2"   | 2"       | 3"       | 4"       | 6"       | 8"       | 10"      | 12"      |
|---------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| DN                        | 25       | 40       | 50       | 75       | 100      | 150      | 200      | 250      | 300      |
| SLING RATED CAPACITY (Kg) | 500      | 500      | 1000     | 1000     | 1000     | 4000     | 4000     | 6000     | 6000     |
| CODE                      | OGHB0100 | OGHB0150 | OGHB0200 | OGHB0300 | OGHB0400 | OGHB0600 | OGHB0800 | OGHB1000 | OGHB1200 |



TYPE MR  
with Metal Ring  
(UP 2")



TYPE SS  
with Simple Sling  
(ABOVE 2")