



JETTING HOSE

STANDARD

ABS/DNV

APPLICATION

Jetting hose is high-pressure flexible connection between main deck of platform and high pressure water systems used to break the suction between the jackup feet (spud cans) and ocean floor prior to lifting the legs.

HOSE STRUCTURE

Tube: Nitrile rubber based liner, oil resistance, seawater resistance, high temperature resistance and ageing resistance.

REINFORCEMENT

High tension steel cable. Cover: Neoprene rubber based cover, fire-proof, wear resistance, oil resistance, ozone & ageing resistance, UV resistance, which is applicable to marine environment.

TEMPERATURE RANGE

-30°C to +100°C.

MAXIMUM CONTINUOUS LENGTH

70m

PRODUCT CODE	ID (inch)	ID (mm)	OD (inch)	OD (mm)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	SAFETY COEFFICIENT	MBR (m)	WEIGHT (kg/m)
OGJET0512K	2	51	3.03	77	140	2000	560	8000	4	900	7.0
OGJET0632K	2-1/2	64	3.58	91	140	2000	560	8000	4	900	9.5
OGJET0762K	3	76	4.61	117	140	2000	560	8000	4	1200	15.5
OGJET0902K	3-1/2	89	4.84	123	140	2000	560	8000	4	1400	15.8
OGJET1022K	4	102	5.24	133	140	2000	560	8000	4	1400	16.0
OGJET1272K	5	127	6.69	170	140	2000	560	8000	4	1450	28.5
OGJET1522K	6	152	7.68	195	140	2000	560	8000	4	1500	35.5
OGJET0513K	2	51	3.39	86	210	3,000	840	12,000	4	900	10.4
OGJET0633K	2-1/2	64	3.94	100	210	3,000	840	12,000	4	900	12.4
OGJET0763K	3	76	4.37	111	210	3,000	840	12,000	4	1,200	15.1
OGJET0903K	3-1/2	89	5.00	127	210	3,000	840	12,000	4	1,400	19.2
OGJET1023K	4	102	5.47	139	210	3,000	840	12,000	4	1,400	21.4
OGJET1273K	5	127	7.36	187	210	3,000	840	12,000	4	1,500	41.5
OGJET1523K	6	152	8.50	216	210	3,000	840	12,000	4	1,600	58.0