

FLEX LANCE SELECTION GUIDE

(All hoses and end fittings show actual size)

Duralife™ Outer Cover for Superior Abrasion Resistance

Blast-Pro® Compact End Fitting for tight bends and small tubes

OD SIZE

0.36"		3/2 Duralife Flex™ (0.13" I.D.) 0.36" Maximum End Fitting O.D. 14,500 P.S.I. Working Pressure End Fittings: 1/16"MNPT
0.39"		4/2 Duralife Flex™ (0.16" I.D.) 0.39" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/16"MNPT 1/16"FNPT 1/8"MNPT
0.47"		5/2 Duralife Flex™ (0.20" I.D.) 0.47" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/8"MNPT 1/8"FNPT
0.55"		6/2 Duralife Flex™ (0.25" I.D.) 0.55" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/4"MNPT
0.70"		8/2 Duralife Flex™ (0.32" I.D.) 0.70" Maximum End Fitting O.D. 12,000 P.S.I. Working Pressure End Fittings: 1/4"MNPT 3/8MNPT
0.50"		5/3 Duralife Flex™ for Extreme Service (0.20" I.D.) 0.50" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/8"MNPT 1/8FNPT
0.60"		6/3 Duralife Flex™ for Extreme Service (0.25" I.D.) 0.60" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/4"MNPT
0.50"		5/2OK Stainless Steel Outer Cover (0.20" I.D.) 0.50" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/8"MNPT 1/8 FNPT
0.60"		6/2OK Stainless Steel Outer Cover (0.25" I.D.) 0.60" Maximum End Fitting O.D. 15,000 P.S.I. Working Pressure End Fittings: 1/4"MNPT
0.47"		3/4 (0.13" I.D.) 0.47" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 1/4"-28 Medium Pressure Male Left Hand or Right Hand Threads
0.49"		4/4 (0.16" I.D.) 0.49" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 1/4"-28 MP/M or F Left Hand or Right Hand
0.49"		5/4 Blast Pro® (0.20" I.D.) 0.49" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 1/4"-28 OR 3/8" -24 MP/M or F Left Hand or Right Hand Threads
0.57"		6/4 Blast Pro® (0.25" I.D.) 0.57" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 3/8" -24 MP/M or F Left Hand or Right Hand Threads
0.67"		8/4 Blast Pro® (0.32" I.D.) 0.67" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 9/16" -18 MP/M or F Left Hand or Right Hand Threads
0.81"		10/4 Blast Pro® (0.40" I.D.) 0.81" Maximum End Fitting O.D. 20,000 P.S.I. Working Pressure End Fittings: 9/16" -18 MPF Left Hand or Right Hand Threads